


# 8 channels PT100/PT1000 RS485 module

## Manual



**Model: CWT-TM-8PT**



### Basic parameters

Power supply	DC8~30V
Power consumption	9mA@30V, 12mA@24V, 23mA@12V, 33mA@8V
Input	<ul style="list-style-type: none"> <li>Input sensor type: PT100 or PT1000</li> <li>Measure range: -180°C ~ +650°C</li> <li>Resolution 0.1°C; accuracy 0.25°C</li> <li>Support two and three wire connections</li> <li>Supports disconnection and short circuit detection</li> </ul>
Output	RS485 (Modbus RTU protocol) , isolation design
Working environment	-30~+55°C / 0 -95%RH
Material	ABS
mounting type	35mm Din-rail
Dimensions	88*72*59mm

### Terminal description


Terminals	description
+V	Power +
GND	Power -
RTDx+	PT100/1000 +
RTDx-	PT100/1000 -
GND	PT100/1000 GND
A (D+)	RS485 +
B (D-)	RS485 -

## PT100/PT1000 wiring

Three wires connection	Two wires connection Need to short RTD(n)- and GND
	

**Note:** The PGND is completely isolated from the power negative.

## Size



RS485 communication Default parameters: 9600,n,8,1

Default device address is 1

Modbus RTU protocol

### 1. Parameter register map

Function code: 03H (read), 06H (write)

Address (hex)	Byte order	Meaning	Description	Property
10	LO	Communication parameters	BIT<7:5> reserve BIT<4:3> 00=none 01=even 10=odd (11= odd) BIT<2:0> 000=9600 001=1200 010=2400 011=4800 100=9600 101=14400 110=19200 initial value: 00	RW
	Hi	address	1-250	RW
		initial value: 01		

### Set slave ID

E.g., set slave ID=2, baud=9600, parity=none,

Master sends

Address	Function Code	Start Address (Hi)	Start Address (Lo)	ID	baud and parity	Error Check (Lo)	Error Check (Hi)
0x01	0x06	0x00	0x10	0x02	0x04	0x88	0xAC

ID=02 (HEX) = 2 (DEC)

Band and parity=0000 0100 (BIN) = 04 (HEX)

Sensor responds:

Address	Function Code	Start Address (Hi)	Start Address (Lo)	ID	baud and parity	Error Check (Lo)	Error Check (Hi)
0x01	0x06	0x00	0x10	0x02	0x04	0x88	0xAC

### Enquiry slave ID, baud and parity

Master sends

Address	Function Code	Start Address (Hi)	Start Address (Lo)	Number of Points (Hi)	Number of Points (Lo)	Error Check (Lo)	Error Check (Hi)
0x00	0x03	0x00	0x10	0x00	0x01	0x84	0x11

Sensor responds:

Address	Function Code	Number of Points	ID	baud and parity	Error Check (Lo)	Error Check (Hi)
0x01	0x03	0x02	0x01	0x0B	0xF8	0x13


ID=01 (HEX) = 1 (DEC)

baud and parity =0B (HEX) = 0000 1011 (BIN)

so baud = 011 = 4800, parity = 01 = even


### Set id by Modbus poll

1. Read Parameter register (address = 10 Hex = 16 )



2. E.g., Set id=2, baud=9600, parity=none (corresponding value= 02 04 H = 516)

Double click register value, enter 516 and click send



## 1. Data register map

Function code: 03H (read)

Address (hex)	PLC address	Description	Format		Number of bytes	Property
30H	40049-40050	Channel 1	Float32		4	R
32H	40051-40052	Channel 2			4	R
34H	40053-40054	Channel 3			4	R
36H	40055-40056	Channel 4			4	R
38H	40057-40058	Channel 5			4	R
3AH	40059-40060	Channel 6			4	R
3CH	40061-40062	Channel 7			4	R
3EH	40063-40064	Channel 8			4	R
68H	40105	Channel 1	UINT16	Scale: 0.1	2	R
69H	40106	Channel 2			2	R
6AH	40107	Channel 3			2	R
6BH	40108	Channel 4			2	R
6CH	40109	Channel 5			2	R
6DH	40110	Channel 6			2	R
6EH	40111	Channel 7			2	R
6FH	40112	Channel 8			2	R

E.g., read channel 1- channel 8 in UINT16

Master sends

Address	Function Code	Start Address (Hi)	Start Address (Lo)	Number of Points (Hi)	Number of Points (Lo)	Error Check (Lo)	Error Check (Hi)
0x01	0x03	0x00	0x68	0x00	0x08	0XC5	0XD0

Sensor responds:

Address	Function Code	Number of byte	value	Error Check (Lo)	Error Check (Hi)
0x01	0x03	0x10	0x00 0XDE 0x00 0XDF 0x00 0xE0 0x00 0xE2 0x00 0xE8 0x00 0xEB 0x01 0x4C 0x01 0x41	0x5B	0x6A

Channel 1: DE(HEX) = 222 (DEC), Channel 1 is 22.2

Channel 2: DF (HEX) = 223(DEC), Channel 2 is 22.3

Channel 3: E0(HEX) = 224 (DEC), Channel 3 is 22.4

Channel 4: E2 (HEX) = 226 (DEC), Channel 4 is 22.6

Channel 5: E8 (HEX) = 232 (DEC), Channel 5 is 23.2

Channel 6: EB (HEX) = 235 (DEC), Channel 6 is 23.5

Channel 7: 14C (HEX) = 332(DEC), Channel 7 is 33.2

Channel 8: 141 (HEX) = 321(DEC), Channel 8 is 32.1

E.g., read channel 1 - channel 8 in Float32

Master sends

Address	Function Code	Start Address (Hi)	Start Address (Lo)	Number of Points (Hi)	Number of Points (Lo)	Error Check (Lo)	Error Check (Hi)
0x01	0x03	0x00	0x30	0x00	0x10	0X44	0x09

Sensor responds:

Address	Function Code	Number of byte	value	Error Check (Lo)	Error Check (Hi)
0x01	0x03	0x20	0x41 0xB3 0xA7 0x52 0x41 0xE5 0x3B 0x99 0x42 0x03 0x8C 0xE7 0x41 0xC7 0xE6 0x9B 0x41 0xBB 0x9B 0xDA 0x41 0xED 0x3C 0x02 0x41 0xF5 0x36 0x11 0x41 0xDF 0xA1 0xFF	0x77	0xC9

Channel 1: 41 B3 A7 52 (IEEE) = 22.4567 (DEC), Channel 1 is 22.4567

Channel 2: 41 E5 3B 99 (IEEE) = 28.6541 (DEC), Channel 2 is 28.6541

Channel 3: 42 03 8C E7 (IEEE) = 32.8876 (DEC), Channel 3 is 32.8876

Channel 4: 41 C7 E6 9B (IEEE) = 24.9876 (DEC), Channel 4 is 24.9876

Channel 5: 41 BB 9B DA (IEEE) = 23.4511 (DEC), Channel 5 is 23.4511


Channel 6: 41 ED 3C 02 (IEEE) = 29.6543 (DEC), Channel 6 is 29.6543

Channel 7: 41 F5 36 11 (IEEE) = 30.6514 (DEC), Channel 7 is 30.6514

Channel 8: 41 DF A1 FF (IEEE) = 27.9541 (DEC), Channel 8 is 27.9541

## Read by Modbus poll

E.g., read channel 1- channel 8 in UINT16



The screenshot shows the Modbus Poll software interface. In the background, a table lists channel data with columns for Alias, Address, and Value. The 'Read/Write Definition' dialog box is open in the foreground, showing the configuration for reading data from the PLC. The dialog includes fields for Slave ID (1), Function (03 Read Holding Registers (4x)), Address (105), and Quantity (8). The 'Scan Rate' is set to 1000 [ms]. The 'View' section shows 'Rows' set to 10 and 'PLC Addresses (Base 1)' checked. The 'Read/Write Once' button is also visible.

Modbus Poll - Mbpoll1

File Edit Connection Setup Functions Display View Window Help

05 06 15 16 17 22 23 TC ? ?

Mbpoll1

Tx = 194: Err = 29: ID = 1: F = 03: SR = 1000ms

	Alias	4x0100	Alias	4x0110
1				332
2				321
3				
4				
5		222		
6		223		

Communication Traffic

Exit Continue Clear Save Copy Log ☐ Stop on Error ☐ Time stamp

1 Tx:000014-01 03 00 68 00 08 C5 D0  
 Rx:000015-01 03 10 00 DE 00 DF 00 E0 00 E2 00 E8 00 EB 01 4C 01 41 5B 6A

For Help, press F1. Port 1: 9600-8-N-1

### Read channel 1 - channel 8 in Float32

Modbus Poll - Mbpoll1

File Edit Connection Setup Functions Display View Window Help

05 06 15 16 17

Mbpoll1

83: Err = 12: ID = 1: F = 03: SR = 1000ms

Alias	4x0040	Alias	4x0050
			16869
			15257
			16899
			36071
			16839
			59035
			16827
			39898
	16819		16877
	42834		15362

Read/Write Definition

Slave ID: 1 OK Cancel

Function: 03 Read Holding Registers (4x)

Address: 49 Protocol address. E.g. 40011 -> 10

Quantity: 16

Scan Rate: 1000 [ms] Apply

Disable

☐ Read/Write Disabled

☐ Disable on error Read/Write Once

View

Rows

☒ 10 ☐ 20 ☐ 50 ☐ 100 ☐ Fit to Quantity

☐ Hide Alias Columns ☒ PLC Addresses (Base 1)

☐ Address in Cell ☐ Enron/Daniel Mode

For Help, press F1. Port 1: 9600-8-N-1

